SEMICONDUCTOR

S8050

NPN Plastic-Encapsulate Transistors

FEATURES

· Epoxy meets UL-94 V-0 flammability rating
· Complementary to S8550
· Power Dissipation of 300mW
· High Stability and High Reliability

SOT-23



MECHANICAL DATA

· Case:SOT-23(TO-236)
· Terminals:Plated solderable per MIL-STD-750,method 2026
· Mounting Position: Any
Marking:J3Y



MAXIMUM RATINGS(T_A=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Value
Collector-Emitter Voltage	V_{CEO}	V	25
Collector-Base Voltage	V_{CBO}	V	40
Emitter-Base Voltage	V_{EBO}	V	5
Collector Current, Continuous	I_C	mA	500
Collector Power Dissipation	P_D	mW	300
Operation Junction Temperature	T_J	℃	-55 to +150
Storage Temperature	T_{STG}	℃	-55 to +150
Thermal resistance From junction to ambient	$R_{\Theta JA}$	℃/W	417

Download from alldatasheet.com

ELECTRICAL CHARACTERISTICS(T_A=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Conditions	Min	Max
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	V	I_C=1.0mA,I_B=0	25	---
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	V	I_C=100μA,I_E=0	40	---
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	V	I_E=100μA,I_C=0	5	---
Collector cut-off Current	I_{CBO}	nA	V_{CB}=40V,I_E=0	---	100
Collector cut-off Current	I_{CEO}	nA	V_{CE}=20V,I_B=0	---	100
Emitter cut-off Current	I_{EBO}	nA	V_{EB}=5V,Ic=0	---	100
DC Current Gain	h_{FE}		I_C=1mA,V_{CE}=1.0V	---	---
	$h_{FE(1)}$		I_C=50mA,V_{CE}=1.0V	120	400
	$h_{FE(2)}$		I_C=500mA,V_{CE}=1.0V	50	---
Collector-Emitter Saturation Voltage	VCE(sat)	V	I_C=10mA,I_B=1.0mA	---	---
			I_C=500mA,I_B=50mA	---	0.6
Base-Emitter Saturation Voltage	VBE(sat)	V	I_C=10mA,I_B=1.0mA	---	---
			I_C=500mA,I_B=50mA	---	1.2
Output Capacitance	Cob	pF	V_{CB}=6V,f=1.0MHz,I_E=0	---	---
Input Capacitance	Cib	pF	V_{EB}=0.5V,f=1.0MHz,I_C=0	---	---
Current Gain-Bandwidth Product	f_T	MHz	I_C=20mA,V_{CE}=6V f=30MHz	150	---
Noise Figure	NF	dB	V_{CE}=5.0V,f=1.0kHz, I_C=100μA, R_S=1. 0K	---	---

CLASSIFICATION OF $h_{FE(1)}$

Rank	L	H	J
Range	120–200	200–350	300–400

AVAILABALE PACK INFORMATION

Product code	Pack	Reel Size (mm)	Quantity (Pcs/reel)	Quantity (pcs/box)	Quantity (pcs/carton)
S8050	T/R	Φ180	3K	30K	120K

Download from alldatasheet.com

Characteristics(Typical)













Download from alldatasheet.com





Outline Dimensions

SOT-23



Dimensions in inches and (millimetrers)

Suggested pad layout



Dimensions in millimetrers

Download from alldatasheet.com

Friendship Reminder

■ JiNan JingHeng (hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.

■ Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

■ JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.

■ JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

■ No license is granted by implication or otherwise under any intellectual property rights of JH.

■ JH is products are not authorized for use as critical components in life support devices or systems without express written approval of JH.

Download from alldatasheet.com